



# DP-280 V

## DMR Digital two-way portable radio



Digital mode, single call、group call、all call function  
Built in CTCSS/DCS

- English Voice Prompt
- Power Save/Low Power Alarm
- Channel Scanning/Priority Scanning
- Emergency Call
- Private/Grup/All Call
- Lone Worker
- Programming Password
- Wide/Narrow Selection
- High/Low Power
- TOT
- Dual time slot



Patented product, counterfeiting not allowed.  
Patent: 201430207600.6

# DP-280 V

## DMR Digital two-way portable radio



### Main Functions

- Use Time-Division Multi-Access(TDMA) digital technology which doubles the number of users on a single licensed 12.5KHz channel. Comply with DMR digital protocol.
- 8 hours recoding function optional
- Dual time slot
- Private call, group call, and all call
- Built-in CTCSS/DCS
- English Voice Prompt
- Power Save/Low Power Alarm
- Channel Scanning/Priority Scanning
- Wide/Narrow Selection
- High/Low Power
- Emergency Alarm
- TOT

General	Transmitter	Receiver			
Frequency range	VHF: 136-174MHz	Output power	High: ≤5W (HI) Low: ≤1W (Low)	Analog sensibility	0.35uV/-116dBm(20dB SINDA) 0.22uV/-120dBm(Type)
Channel	32 Channels	Frequency Stability	+/-1.0PPM	Digital sensibility	0.3uV/-117.4dBm (BER 5%) 0.22uV/-110dBm (BER 1%)
Channel Spacing	12.5KHz	Adjacent Channel Power	≤-60dB	Co-channel Rejection	> -12dB
Operating Voltage	7.4V	Free Time Slot Power	TDMA: ≤57dBm	Adjacent Channel Selectivity	TIA603C:65dB ETSI:60dB
Battery Type	Li-ion	Hum and Noise	-40dB@12.5KHz	Spurious Response	TIA603C:75dB ETSI:70dB
Operating Temperature	-30℃+60℃	Spurious Radiation	Antenna: 9KHz-1GHz ≤-36dBm 1GHz-12.75GHz ≤-30dBm	Rated audio power	1W
Store Temperature	-40℃+85℃	FM Modulation Mode	12.5KHz: 11K0F3E	Audio response	=1dB~-3dB
Antenna Impedence	50Ω	4FSK Digital Mode	12.5KHz(data only):7K60FXD 12.5KHz(data +voice): 7K60FXE	Rated audio distortion	3%(Type)
Audio Output Power	≤1000mW@16Ω	Modulation Maximum Deviation	2.5KHz@12.5KHz	Spurious Radiation	Antenna: 9KHz-1GHz ≤-57dBm 1GHz-12.75GHz ≤-47dBm
Battery capacity	2000mAh standard Li-ion battery	Nonactive Slot Power	-57dBm		
Dimension (H*W*D)	128*61*38mm	Digital Protocol	ETSI TS 102 361-1 -2 -3		
Weight	258g	Vocoder Type	AMBE+2TM		
		Audio Response	+1dB~-3dB		
		Modulation BER(Bit Error Rate)	≤5%		

### Standard Accessories



Battery Pack



Charger



Adapter



Antenna



Belt Clip



Strap Wire

More optional accessories please refer to our website: [www.tyt888.com](http://www.tyt888.com)



**TYT Electronics Co.,LTD**

Block 39-1, Optoelectronics-information industry base,  
Nan'an, Quanzhou, Fujian E-mail: [tyt@tyt888.com](mailto:tyt@tyt888.com)

[Http://www.tyt888.com](http://www.tyt888.com)

Nationwide Toll Free No.: **400-699-8858**



Approved by GB/T19001-2008 ISO9001:2008  
ID: 01609Q21255R0M