

Main Features:

FCC & CE

- Startup Password
- Definable Device Name (send the name at the end of calling)
- Customized Startup Logo / Greetings
- Voice Prompt
- 1024+2*VFO Channel, 250 Zones Supported
- Talk Around and Reverse Frequency
- High / Low Power Switching
- TOT / VOX / Scanning/Monitor
- Editable Channel Name
- Timed Lock & Auto-lock
- DTMF Setting (Analog Mode)
- Definalbe keys

- Dual Standby
- Backlight Level
- NOAA / FM

DMR Functions:

- 2000 Digital Contact List
- 256 Receiving Group List
- SMS
- Stun / Kill / Activation
- 131 × 62 × 38 about 275g
- Remote Monitor



Specifications:

Frequency Range	VHF: 136-174MHz
Working voltage	7.4V DC
Working temperature	-20°C ~ +60°C
Working Mode	Same frequency simplex,different frequency simplex

The approval of the National Telecom Regulatory Authority (NTRA) must be obtained before buying or selling.

Channel storage	1024 Channels +2*VFO channels
Frequency Stability	±2.5ppm
Antenna Impedance	50 Ω
Channel spacing	Analog:25kHz/12.5kHz Digital:12.5K
Modulation Type	Analog: F3E Digital: 4FSK
Maximum Frequency Deviation	≤± 5KHz(W), <2.5KHz(N)
SNR (W/N)	-45dB/ -40dB
TX Current	≤1500mA
RF Modulation Sensitivity	
Modulation distortion	<5%
Receiving Sensitivity	0.22μV/ 0.25μV 12dB SINAD
Audio Power	≤1W (16Ω)
Audio distortion	<5%
Inter modulation (W/N)	65dB/ 60dB
Standby current	≤350mA
RX Current	≤70mA
Battery Capacity	2000mAh-2800mAh

DMR Iradio DP-580 V Made especially for Egypt

The approval of the National Telecom Regulatory Authority (NTRA) must be obtained before buying or selling.